



Engage The Power of We™

# Avaya Scopia® XT4300 Room System

## Cost-Effective HD Video Collaboration

### Highlights

- Efficient Full HD Performance
- Outstanding Value
- Intuitive and Easy-to-Use
- Embedded Multi-party Conferencing
- All-in-one Solution



The Avaya Scopia® XT4300 offers outstanding value and cost-effective full HD video collaboration specifically designed for the needs of small and mid-size conference rooms as well as users that don't require all the features offered in Scopia advanced room system solutions. The Scopia XT4300 system is incredibly powerful and includes many features often found with costly upgrades in other vendor offerings.

The Scopia XT4300 is well equipped and includes dual HD 1080p/60fps live video and content, HD audio, H.264 High Profile and Scalable Video Coding (SVC), along with a wide-angle PTZ camera. A range of affordable options is available including an embedded four participant MCU delivering continuous presence multi-party conferencing, Scopia Desktop and Mobile collaboration, dual display support, and control via an Apple iPad device for enhanced meeting management. The Scopia XT4300 is a natural fit for today's businesses with a user interface built for simplicity and a modern design to complement any conference room.





deployment. A range of affordable options to enhance the system is also available.

## Intuitive and Easy-to-Use

The Scopia XT4300 has been designed with the end user in mind. It delivers instant, intuitive and effective meeting control with little or no training required. With Microsoft Exchange calendar support, users can join meetings directly from the integrated system calendar. The advanced on-screen participants list gives leaders full meeting moderation. And to further extend its user functionality, the system is available with optional control via an Apple iPad device.

## Embedded Multi-party Conferencing

The Scopia XT4300 offers optional embedded multi-party conferencing with support for up to four participants. This dedicated multipoint collaboration capability is always at the ready for impromptu group meetings in today's fast-paced business environment.

## All-in-one Solution

The Scopia XT4300 is also offered as a unique all-in-one video conferencing solution combining its room system capabilities with embedded four-way multi-party conferencing, Scopia Desktop and Mobile for remote participants and bring your own device (BYOD) initiatives, along with firewall traversal into an easily deployed all-in-one video conferencing and collaboration solution.

With more than 100 years as a leader in communications, Avaya can help your company maximize productivity with the communications solutions specific to the needs of your workforce.

## Efficient Full HD Performance

The Scopia XT4300 delivers efficient full HD performance featuring H.264 High Profile for bandwidth efficiency and H.264 SVC for high quality images, even in unpredictable network environments. The XT4300 also offers dual 1080p 60fps live HD video and HD content, HD audio and optional Apple iPad Multi-Touch control.

## Outstanding Value

The Scopia XT4300 offers outstanding value including a comprehensive set of features that can be costly upgrades in other vendor offerings. Dual 1080p 60fps full HD video, H.264 High Profile, H.264 SVC, and a wide angle PTZ camera are all included for cost-effective video communications

# Scopia XT4300 Specifications

## Communications

- IP: H.323, SIP (RFC 3261)
- ISDN<sup>1</sup> Supported through Scopia Gateway
- Bit rate: H.323, SIP: up to 4/12<sup>1</sup> Mbps
- H.320: up to 2 Mbps
- MCU compatibility: H.243, H.231

## Video

- 2 simultaneous 1080p 60fps channels: camera + content
- H.263, H.263+, H.263++, H.264, H.264 High Profile, H.264 SVC
- Dual: H.239 (H.323); BFCP (SIP)
- **HDMI input formats**
  - 1920 x 1080p @ 25, 30, 50, 60fps
  - 1280 x 720p @ 25, 30, 50, 60fps
  - 720 x 576p @ 50fps
  - 720 x 480p @ 60fps
  - 640 x 480p @ 60fps
- **Live video encoding formats**
  - 1920 x 1080p @ 25, 30, 50, 60fps
  - 1280 x 720p @ 25, 30, 50, 60fps
  - 1024 x 576p @ 25, 30fps: w576p
  - 848 x 480p @ 25, 30fps: w480p
  - 768 x 448p @ 25, 30fps: w448p
  - 704 x 576p @ 25, 30fps: 4CIF
  - 704 x 480p @ 25, 30fps: 4SIF
  - 624 x 352p @ 25, 30fps: w352p
  - 576 x 336p @ 25, 30fps
  - 512 x 288p @ 25, 30fps: wCIF
  - 416 x 240p @ 25, 30fps: w240p
  - 400 x 224p @ 25, 30fps
  - 352 x 288p @ 25, 30fps: CIF
  - 352 x 240p @ 25, 30fps: SIF
- **DVI input formats**
  - 1920 x 1080p @ 60fps
  - 1600 x 900p @ 60fps (digital only)
  - 1440 x 900p @ 60fps: WSXGA
  - 1280 x 1024p @ 60, 75fps: SXGA
  - 1280 x 960p @ 60, 85fps: SXGA

1280 x 768p @ 60fps: WXGA  
1280 x 800p @ 60fps: WXGA  
1280 x 720p @ 60fps  
1024 x 768p @ 60, 70, 75 fps: XGA  
800 x 600p @ 60, 72, 75fps: SVGA  
640 x 480p @ 72, 75fps: VGA

## • PC content encoding formats:

Up to 1080p @ 60fps

## • HDMI output formats

1920 x 1080 @ 25, 30, 50, 60fps  
1280 x 720 @ 50, 60fps

## Camera

- Resolution: 1080p 60fps
- Presets: 122
- Field of View (H): 16° - 70°
- PAN / Tilt: ± 100° / ± 25°
- Zoom (standard): 5x (optical)
- Zoom (optional): 5x optical, 3x digital, 15x total
- Far End Control: H.224, H.281
- Ceiling mount and image vertical flip supported

## Recording<sup>1</sup>

- Recording on USB key / disk (with dual display systems, both displays show the same images while recording)
- USB disk formats: FAT32, EXT2, EXT3, EXT4
- Recording formats: MP4 file

## Audio

- Acoustic echo cancellation
- Adaptive post filtering
- Audio error concealment
- Automatic Gain Control (AGC)
- Automatic noise suppression
- **Frequency response:**
  - G.711: 300 - 3,400 Hz
  - G.728: 50 - 3,400 Hz<sup>1</sup>
  - G.729A: 50 - 3,400 Hz<sup>1</sup>

G.722, G.722.1: 50 - 7,000 Hz  
G.722.1 Annex C: 50 - 14,000 Hz  
AAC-LD: 50 - 14,000 Hz  
AAC-LC: 50 - 14,000 Hz  
G.719: 50 - 20,000 Hz

## Microphone

- 180° range
- Frequency response: 50 - 22,000 Hz

## Audio/Video Interfaces

### • Video inputs:

1 x HDMI  
1 x DVI-I

### • Video outputs:

1 x HDMI for main display  
1 x HDMI for second display<sup>1</sup>

### • Audio inputs:

1 x HDMI  
1 x Microphone Array Pod (RJ-11)  
1 x 3.5 mm (1/8") line in jack for audio source (analog / digital with mini-TOSLINK adapter)

### • Audio outputs:

2 x HDMI (second output optional)  
1 x 3.5 mm (1/8") line out jack (analog / digital with mini-TOSLINK adapter)

## USB Ports<sup>2</sup>

- 1 x USB2
- 1 x USB3

## Network Features

- IPv4 and IPv6 simultaneous support
- Auto Gatekeeper discovery
- QoS support: IP Precedence, IP Type of Service (ToS), Differentiated Services (diffserv)
- Avaya NetSense bandwidth adaptation for high quality over unmanaged networks
- DTMF tones: H.245, RFC2833
- SNTP date and time synchronization
- **IP adaptive packet management**
  - Flow control
  - Packet Loss based down-speeding
  - Packet Loss recovery policies

## Network Protocols

- DHCP, DNS, HTTP, HTTPS, RTP/RTCP, SNTP, STUN, TCP/IP, TELNET, TFTP, 802.1Q, 802.1X

## Network Interfaces

- 2 x 10/100/1000 Base-T full-duplex (RJ-45) (2nd GLAN is optional)

## Scopia XT4300 Options

- 15x Zoom Upgrade (5x Optical, 3x Digital)
- Second HD Display Support
- 4 Port Embedded 1080p30 MCU
- Scopia Desktop & Mobile Support
- Scopia XT 3-way Microphone Array Pod
- Scopia Premium XT 3-way Microphone Array Pod
- Recording on USB Key / Disk
- Scopia Control Application for Apple iPad device
- 2nd GLAN Enable
- Extended IP Bit Rate: Multipoint = 12 Mbps, P2P = 10/8 Mbps (SIP/H.323)
- Advanced Audio Codec Pack (G.728 and G.729A)

## Support Services

Avaya offers a full set of services to help maximize a video investment. Strategic and technical consulting along with deployment and customization services help ensure that video collaboration rollouts are successful and aligned to business requirements.

Avaya Video Support Services maximizes up time with software updates, upgrades, remote maintenance and expert repairs.

## About Avaya

Avaya is a leading, global provider of customer and team engagement solutions and services available in a variety of flexible on-premise and cloud deployment options. Avaya's fabric-based networking solutions help simplify and accelerate the deployment of business critical applications and services. For more information, please visit [www.avaya.com](http://www.avaya.com).

## Scopia XT4300 Specifications (cont.)

### Firewall Traversal

- Auto NAT discovery HTTP and STUN
- H.460.18, H.460.19
- "Keep Alive" packet time configurable

### Camera Interface

- VISCA RS232 for PTZ control (Mini-DIN 8-pin)

### User Interface

- 24 language on-screen user interface
- Infrared remote control
- API for endpoint control
- Scopia Control application for Apple iPad device<sup>1</sup>
- Microsoft Exchange calendar integration

### Directory Service & Address Book

- LDAP Client (H.350)
- Receive global address book from LDAP Server including Scopia Management

### Multipoint Control Unit<sup>1</sup>

- H.323 and SIP mixed mode
- 4 HD continuous presence participants
- Support for Scopia Desktop and Mobile<sup>1</sup>
- Dial-in / Dial-out capabilities
- Encryption<sup>3</sup>
- Automatic continuous presence layouts
- Dual-video from any site

### Security Features

- Embedded encryption<sup>3</sup>
- H.323 security per H.235v3/Annex D
- SIP security per SRTP and TLS, enciphering up to AES-256
- SIP "Digest" authentication (MD5)
- RTP media enciphering with AES-128
- Public-Key including Diffie-Hellman (1024 bits), RSA (up to 4096 bits)
- Cryptographic hash (up to SHA-512)
- Web access via HTTP
- API access via SSH
- Selective enable / disable of IP features

### Web Management

- Configuration, call, diagnostics and management functions are accessible with Internet Explorer 8.0+, Firefox 3.6+, Safari 5.0+, Chrome 11.0+, Opera 11+

### Power Supply

- 100-240 VAC, 50-60 Hz, 2.5 A Max.

### Physical Characteristics

#### • Horizontal / Vertical Mounting:

- W: 29.0 cm (11.4")
- D: 16.5 cm (6.5")
- H: 4.0 cm (1.6")
- Weight: 2.4 kg (5.3 lb)

#### • Camera

- W: 26.7 cm (10.5")
- H: 15.6 cm (6.1")
- D: 12.4 cm (4.8")
- Weight: 1.3 kg (2.8 lb)


#### • Microphone Pod:

- W: 12.0 cm (4.7")
- Weight: 0.4 kg (0.9 lb)

<sup>1</sup> Optional.

<sup>2</sup> USB supports recording, firmware upgrade, USB to serial adapter for control, limited headsets and cameras (USB2 camera support).

<sup>3</sup> Encryption is subject to local regulations and in some countries is restricted or limited. Please contact your Avaya representative for details.



## Learn More

To learn more and to obtain additional information such as white papers and case studies about the Avaya Scopia XT4300 Room System, please contact your Avaya Account Manager or Authorized Partner or visit us at [www.avaya.com](http://www.avaya.com).

