

## 8-Line Professional Carrier-Grade IP Phone GRP2624

Part of the GRP series of Carrier-Grade IP Phones, the GRP2624 is a professional 8-line model designed with zero-touch provisioning for mass deployment and easy management. It features a sleek design and a suite of next-generation features including: 5-way voice conferencing to maximize productivity, integrated Wi-Fi, Bluetooth support, full HD audio on both the speaker and handset to provide the utmost clarity, EHS support for Plantronics headsets and USB to support Grandstream's GUV Series headsets. The GRP2624 is compatible with the GBX20 Extension Module that adds functionality, versatility and flexibility with up to 40 contacts per module and support for up to 160 contacts by connecting 4 extension modules. The GRP series includes carrier-grade security features to provide enterprise-level security, including secure boot, dual firmware images and encrypted data storage. For cloud provisioning and centralized management, the GRP2624 is supported by Grandstream's Device Management System (GDMS), which provides a centralized interface to configure, provision, manage and monitor deployments of Grandstream endpoints. The GRP2624 is the perfect choice for busy professionals and receptionists who need to manage high call volumes, with advanced functionality. Designed for easy deployment by enterprises, service providers and other high-volume markets, the GRP2624 offers an easy-to-use and easy-to-deploy voice endpoint.



8 lines, 4 SIP accounts



Supported by GDMS which provides a centralized interface to configure, provision, manage and monitor Grandstream devices



Integrated Bluetooth to connect headsets, sync contacts, calendars and more



Full-duplex speakerphone with HD audio to maximize audio quality and clarity



Equipped with noise shield technology to minimize background noise



Dual switched autosensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE



Supports 5-way audio conferencing for easy conference calls



Enterprise-level protection including secure boot, dual firmware images, and encrypted data storage



Swappable faceplate to allow for easy logo customization



Integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)

SIP RFC3261, TCP/IP/UDP, RTP/RTCP, HTTP, HTTPS, ARP, ICMP, DNS(A record, SRV) Network Interfaces Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE Graphic Display 2.8 inch (320x240) TFT color LCD Wi-Fi Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)  Bluetooth Yes, integrated  8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED Indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, Vol-t, V	Protocols/Standards NAPTR), DHCP, PPPOE, TELNET, TFTP, NTP, STUN, SIMPLE, LLDP, LDAP, TR-069, 802.1x, TLS, SRTP, IPV6  Network Interfaces Dual switched auto-sensing 10/100/1000 Mbps Gigabit Ethernet ports with integrated PoE  Graphic Display 2.8 inch (320x240) TFT color LCD  Wi-Fi Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)  Bluetooth Yes, integrated 8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  Auxiliary Port RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets  Voice Codecs and Capabilities Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Graphic Display 2.8 inch (320x240) TFT color LCD  Wi-Fi Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)  Bluetooth Yes, integrated software integrated by the softwar	Integrated PoE  Graphic Display 2.8 inch (320x240) TFT color LCD  Wi-Fi Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)  Bluetooth Yes, integrated  8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  Auxiliary Port RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets  Voice Codecs and Capabilities Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Bluetooth Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)  Bluetooth Yes, integrated  8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with Lessen Les	Wi-Fi Yes, integrated dual-band Wi-Fi 802.11 a/b/g/n/ac (2.4Ghz & 5Ghz)  Bluetooth Yes, integrated  8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  Auxiliary Port RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets  Voice Codecs and Capabilities Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Bluetooth Yes, integrated  8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED Indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  Auxiliary Port  RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets  Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)  Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call logique to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over  Yes, GBXZO  Base Stand Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)  Qo5 Layer 2 Qo5 (802.1Q, 802.1P) and Layer 3 (Tos, DiffServ, MPLS) Qo5  User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Multi-language English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Firmware upgrade via FTP/TETP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100.240V; Output: +12V, TA; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	Bluetooth Yes, integrated  8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  Auxiliary Port  RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets  Voice Codecs and Capabilities  Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Feature Keys  Feature Keys  Softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  Auxillary Port  Rys headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets.  Voice Codecs and Capabilities  Support for G7.29A/B, G.711 µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)  Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance(SCA)/bridged-line-appearance, Call, downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call log(up to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-cl-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over  HD Audio  Extension Module  Extension Module  Seaves  Yes, Cangle positions available, Wall Mountable (Wall Mount *sold separately)  Qost  Layer 2 Qos (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) Qos  User and administrator level passwords, MDS and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Briglish, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Upgrade/Provisioning  Firmware upgrade via FTP/FTTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included:  Input: 100-240V; Output: +12V, 1A;  Integrated Power-over-Ethernet (802.3af)  Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C  Storage: -10°C to 60°C  Humidity: 10% to 90% Non-condensing  Dimension: 220mmx 210mmx 82mm	Feature Keys  8 line keys with up to 4 SIP accounts, 4 XML programmable context sensitive softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets  Voice Codecs and Capabilities  Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Feature Keys  Softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  Auxiliary Port  Ryp headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets  Voice Codecs and Capabilities  Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)  Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance(SCA/)bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call unsting, call log(up to 2000 orecords), XML  LDAP, up to 2000 items), call unsting, call log(up to 2000 orecords), XML  LDAP, up to 2000 items), call unsting, call log(up to 2000 orecords), XML  LDAP, up to 2000 items), call unsting, call log(up to 2000 orecords), XML  LDAP, up to 2000 items), call unsting, call log(up to 2000 orecords), XML  LDAP, up to 2000 items), call unsting, call log(up to 2000 orecords), XML  customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over  HD Audio  Yes, HD handset and speakerphone with support for wideband audio, and dual microphone.  Extension Module  Yes, GBX20  Base Stand  Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)  Qos  Layer 2 Qo5 (802.1Q, 802.1P) and Layer 3 (To5, Diffserv, MPLS) Qos  User and administrator level passwords, MD5 and MD5-sess based authentication, secure boot.  Bulli-language  Upgrade/Provisioning  Firmware upgrade via FIP/FTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°Ct to 40°C  Storage: -10°C to 60	softkeys, 5 navigation/menu keys, 9 dedicated function keys for: MESSAGE(with LED indicator), TRANSFER, HOLD, HEADSET, MUTE, SEND/REDIAL, SPEAKERPHONE, VOL+, VOL-  Auxiliary Port  RJ9 headset jack allowing EHS with Plantronics headsets, USB to support Grandstream's GUV Series headsets and other USB headsets  Voice Codecs and Capabilities  Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Voice Codecs and Capabilities  Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)  Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call log(up to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over  HD Audio  Yes, HD handset and speakerphone with support for wideband audio, and dual microphone.  Extension Module  Yes, GBX20  Base Stand  Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)  Qos  Layer 2 Qos (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) Qos  User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Multi-language  English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Upgrade/Provisioning  Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9-5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	Voice Codecs and Capabilities  Support for G7.29A/B, G.711µ/a-law, G.726, G.722 (wide-band), G723, iLBC, OPUS, in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
Hold, transfer, forward, 5-way conference, call park, call pickup, shared-call-appearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call logicy to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over  HD Audio  Yes, GBX20  Base Stand  Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)  QoS  Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS  User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Multi-language  English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Power & Green Energy Efficiency  Power & Green Energy Efficiency  Power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Humidity: 10% to 90% Non-condensing  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	in-band and out-of-band DTMF (in audio, RFC2833, SIP INFO)
appearance(SCA/)bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call logfup to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server redundancy and fail-over  HD Audio  Pextension Module  Extension Module  Yes, GBX20  Base Stand  Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)  Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS  User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Multi-language  English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Upgrade/Provisioning  Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	Hold transfer forward 5-way conference call park call pickup shared call
Base Stand Yes, GBX20  Base Stand Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)  QoS Layer 2 QoS (802.1Q, 802.1P) and Layer 3 (ToS, DiffServ, MPLS) QoS  User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Multi-language English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Upgrade/Provisioning Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  Package Content GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	appearance(SCA)/bridged-line-appearance(BLA), downloadable phonebook(XML, LDAP, up to 2000 items), call waiting, call log(up to 2000 records), XML customization of screen, off-hook auto dial, auto answer, click-to-dial, flexible dial plan, hot-desking, personalized music ringtones and music on hold, server
Power & Green Energy Efficiency  Operation: 0°C to 40°C  Temperature and Humidity  Package Content  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	
Qos Layer 2 Qos (802.1Q, 802.1P) and Layer 3 (Tos, DiffServ, MPLS) Qos  User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Multi-language English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Upgrade/Provisioning Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Temperature and Humidity Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  Package Content GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	Extension Module Yes, GBX20
User and administrator level passwords, MD5 and MD5-sess based authentication, 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Multi-language English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Upgrade/Provisioning Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Temperature and Humidity Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  Package Content GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	Base Stand Yes, 2 angle positions available, Wall Mountable (Wall Mount *sold separately)
Security  256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control, secure boot.  Multi-language  English, German, Italian, French, Spanish, Portuguese, Russian, Croatian, Chinese, Korean, Japanese and more  Firmware upgrade via FTP/TFTP / HTTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  Package Content  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	
Upgrade/Provisioning Firmware upgrade via FTP/TFTP / HTTPS, mass provisioning using GDMS/TR-069 or AES encrypted XML configuration file.  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  Package Content  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	Security 256-bit AES encrypted configuration file, SRTP, TLS, 802.1x media access control,
Power & Green Energy Efficiency  Universal power adapter included: Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  Package Content  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	
Power & Green Energy Efficiency  Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af) Max power consumption 9.5W (power adapter) or 10.8W (PoE)  Operation: 0°C to 40°C Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  Package Content  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	
Temperature and Humidity  Storage: -10°C to 60°C Humidity: 10% to 90% Non-condensing  Package Content  GRP2624 phone, handset with cord, phone stand, 12V power adapter, network cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	Power & Green Energy Efficiency Input: 100-240V; Output: +12V, 1A; Integrated Power-over-Ethernet (802.3af)
cable, Quick Installation Guide, GPL license  Dimension: 220mmx 210mmx 82mm	<b>Temperature and Humidity</b> Storage: -10°C to 60°C
one weight 300g / Luckage Weight 1200g	Physical Dimension: 220mmx 210mmx 82mm Unit Weight: 880g ; Package Weight:1260g